



DESCRIPTION

UL standard Galvanized Steel RMC Conduit
Threaded on both ends ,available up to 4"
galvanized with one coupling

FEATURES

Galvanized Rigid Steel Conduit provide a
damage-resistant duct for electrical conductors
and cables. this couduit shields internal wires
from magnetic fields and features electroplated
coupling to resist buildup of zinc on the threads.

APPLICATION

Electrical & Construction

SPECIFICATION

1. RMC is thicker than IMC conduit and Electrical metal tubing. threaded on both ends .
2. Size: 1/2" - 4"
3. Material: Steel ,Hot dipped galvanized ,electric galvanized ,Pre-gal
4. Hot-dip galvanized to inhibit white rust and increase corrosion resistance
5. High strength ductile steel for long life and easy bending
6. Provides smooth ,continuous raceways for fast wire-pulling
7. ULlisted to UL6 ,manufactured in accordance with ANSI C80.1
8. Materials :Q195 steel
9. Threaded : NPT
10. Finished by Pre-galvanized ones ,Hot-dip galvanized is also available.

MODEL

size	Outside Diameter		Inside Diameter		Wall Thickness		Length	
inch	inch	mm	inch	mm	inch	mm	feet	mm
1/2"	0.840	21.34	0.632	16.05	0.104	2.64	10	3050
3/4"	1.050	26.67	0.836	21.23	0.107	2.72	10	3050
1"	1.315	33.40	1.063	27.00	0.126	3.20	10	3050
1-1/4"	1.660	42.16	1.394	35.41	0.133	3.38	10	3050
1-1/2"	1.900	48.26	1.624	41.25	0.138	3.51	10	3050
2"	2.375	60.33	2.083	52.91	0.146	3.71	10	3050
2-1/2"	2.875	73.03	2.489	63.22	0.193	4.90	10	3050
3"	3.500	88.90	3.090	78.49	0.205	5.21	10	3050
3-1/2"	4.000	101.60	3.570	90.68	0.215	5.46	10	3050
4"	4.500	114.30	4.050	102.87	0.225	5.72	10	3050